

TAXIWAY LIGHTING

ESTB

Incandescent Elevated Stop Bar
MEDIUM-INTENSITY



Compliance with Standards

FAA: L-862S AC 150/5345-46 (Current Edition).
ETL Certified.

Uses

FAA L-862S

For SMGCS operations (Cat. III) below 600 feet RVR on all lighted taxiways at runway hold lines in conjunction with L-852S in-pavement stop bar light.

Features

- Lens is sealed with weatherproof high-temperature gasket
- Adjustable horizontal and vertical angles
- Easy maintenance, no special tools required for lamp changes
- Lamp: One 150 W/6.6 A quartz PK30d
- Lamp Life: Rated at 500 hours at 6.6 A
- Includes frangible column
- Designed to mount on a standard L-867B light base with 2-inch base plate
- Fixture uses aluminum castings, stainless steel hardware, and is protected with aviation yellow gloss enamel paint

Operating Conditions

Temperature: -40 °F to +131 °F (-40 °C to +55 °C)
Humidity: 0 to 100%
Exposure: Withstands windblown rain, sand, and dust particles, salt-laden atmosphere, solar radiation, and extreme thermal changes

Ordering Code

44A5877 - X

Fixture Height

- 1 = 14 in (35.6 cm)
- 2 = 24 in (61 cm)
- 3 = 30 in (76.2 cm)

Packaging

Quantity per Box	Quantity per Shipment	Dimensions of Cartons	Gross Weight
1 Head Assembly	1 Box	14 × 14 × 13 in	6 lb
		36 × 36 × 33 cm	2.72 kg
1 Head Column	1 Box	1 × 4 × 4 in	1 lb
		2.5 × 10.3 × 10.3 cm	0.45 kg

www.adbsafegate.com

Product specifications may be subject to change, and specifications listed here are not binding. Confirm current specifications at time of order.